Description

Highly effective combination of cleaning and treatment additives for all gasoline injection systems such as K, KE, L-Jetronic and similar systems.

Properties

- removes carbon deposits from intake valves and combustion chamber
- increases operational reliability
- exact dosage
- guarantees low fuel consumption
- optimizes economical use
- reduces pollutant emissions
- cleans the injection system
- cleans and maintains
- assures precise atomization

Technical data

Base	additives, special liquid carrier
Color / appearance	light yellow, clear
Form	liquid
Odor	characteristic
Density at 15 °C	0,82 g/ml
Flash point	>63 °C
Viscosity at 40 °C	<7 mm²/s

Areas of application

Suitable for all gasoline injection systems. Added to the fuel tank after repairs to the fuel system or after changing the filter.

Application

To be added directly into the fuel tank. As a preventive measure, add during each inspection, after repairs on the fuel system and after each Jet-Clean cleaning operation. The product mixes with the fuel automatically.

Contents of can sufficient for max. 70 liters of fuel.

Available pack sizes

500 ml Can sheet metal	21601 GB-AUS
500 ml Can sheet metal	2970 D-NL-F-GR-ARAB
500 ml Can sheet metal	2979 GB-DK-FIN-N-S
500 ml Can sheet metal	20453 D-PL-BG
500 ml Can sheet metal	20917 JP

Available pack sizes

500 ml Can sheet metal 5153 D-GB-I-F-P

Our information is based on thorough research and may be considered reliable, although not legally binding.

PI 45/12/01/2021