

Tacky Lube Spray

Description

Tacky Lube Spray is a synthetic high-quality, heat-resistant, extremely adherent and acceleration-resistant lubricant compound. After the solvent has evaporated, the product leaves an extremely adherent, soft film of grease.

Properties

- outstanding corrosion protection
- excellent creep properties
- highest load-carrying capacity
- high bond strength
- has a lasting effect
- good water resistance
- outstanding thermal stability

Technical data

Base	Syntheseöl, Polymergemisch / synthetic oil, mixed polymers
Color / appearance	hellgelb / pale yellow
Operating temperature range	-30 bis / to +180, kurzfristig bis / intermittent to +200 °C
Propellant	Propan, Butan / propane, butane
Shelf life in original sealed container	60 months

Areas of application

For the preventative regular lubrication of components in vehicles such as hinges, joints, linkages, reversing levers and door catch bands.

Application

Spray an appropriate amount of Tacky Lube Spray onto the cleaned parts to be treated.

Follow the relevant instructions of the vehicle manufacturer.



Available pack sizes

400 ml Can aerosol	4084 D-F-NL
400 ml Can aerosol	2518 D-GB-I-E-P
400 ml Can aerosol	2664 D-PL-H-RO-TR
400 ml Can aerosol	2842 GB-DK-FIN-N-S
50 ml Can aerosol	7607 D-RUS-UA
400 ml Can aerosol	39016 D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.