

Molygen New Generation 5W-40

Description

Low-viscosity high-tech low-friction motor oil with high shear stability. Combined with innovative additive technology and the special Molygen additive. Reliably prevents the formation of deposits, reduces frictional losses in the engine and provides optimum protection against wear. The results are savings in fuel and an extended service life for the engine.

Properties

- outstanding engine cleanliness
- excellent high and low temperature behavior
- friction and wear reducing
- optimum stability to aging
- excellent wear protection
- miscible with all commercially available motor oils
- outstanding lubrication reliability
- high shear stability
- tested for turbochargers and catalytic converters
- instant lubrication after cold start

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

ACEA A3 • ACEA B4 • API SN • BMW Longlife-01 (up to 2018) • Fiat 9.55535-H2 • Fiat 9.55535-N2 • Fiat 9.55535-Z2 • MB 229.5 • Opel GM-LL-B-025 • Porsche A40 • Renault RN 0700 • Renault RN 0710 • VW 502 00 • VW 505 00

Technical data

SAE class (engine oils)	5W-40 SAE J 300
Density at 15 °C	0,850 g/cm ³ DIN 51757
Viscosity at 40 °C	80,7 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,0 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -30°C (CCS)	<= 6600 mPas ASTM D 5293
Viscosity index	180 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D 5481
Pour point	-45 °C DIN ISO 3016



Technical data

Evaporation loss (Noack)	11,0 Gew.-% DIN 51581
Flash point	230 °C DIN ISO 2592
Total base number	11,3 mg KOH/g DIN ISO 3771
Sulfate ash	1,0 - 1,6 g/100g DIN 51575
Color / appearance	grün, fluoreszierend / green, fluorescent

Areas of application

Best for modern gasoline and diesel engines with and without exhaust gas turbochargers. For the protection and value retention of the engine during long intervals between oil changes and with high loads.

Application

Note the vehicle and engine manufacturers' operating instructions. Can be mixed with all commercially-available motor oils. Full effectiveness only achieved when the product is used on its own (i.e. no mixing).

Available pack sizes

1 l Canister plastic	8576 BOOKLET
1 l Canister plastic	21242 ALGERIEN-GB-ARAB-F
1 l Canister plastic	20991 D-GB-CN
4 l Canister plastic	8578 BOOKLET
4 l Canister plastic	20993 D-GB-CN
5 l Canister plastic	8536 BOOKLET
20 l Canister plastic	21329 D-GB-I-E-P
60 l Drum sheet metal	9056 D-GB

Product information

PI 43/05/02/2020



Molygen New Generation 5W-40

Available pack sizes

205 l Drum sheet metal 9057
D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.