## **Product information**

# Battery Clamp Grease Spray



### **Description**

Special grease spray which is compatible with plastics and is formulated for the maintenance and care of vehicle electronic systems, particularly the battery terminals and electrical connectors. Ensures reliable starting and a longer battery life. Offers high corrosion protection and prevents leakage currents. Prevents the contact resistance from increasing during operation and ensures lower loss than with untreated contacts.

## **Properties**

- compatible with plastics
- prevents the contact resistance from increasing during operation and ensures lower loss than with untreated contacts
- good corrosion protection
- prevents leakage currents
- good electronic properties

#### Technical data

Thickener Calciumseife

NLGI number 2

DIN 51818

Color / appearance red

Form aerosol, liquid

Dropping point for the solids 100 °C

**DIN ISO 2176** 

Worked penetration 265-295

DIN 51804

Operating temperature range -30 to +60 °C

Emcor corrosion class 0/0

DIN 51802

Odor characteristic

## Areas of application

Especially for battery terminals and connections in vehicle electronics.

#### Comment

After spraying on, allow a flash-off period of 10 min. before connecting the component to a power supply.

## **Application**

Clean contaminated components and treat with Battery Terminal Grease. Gently shake spray can before use.

#### Available pack sizes

300 ml Can aerosol 3141

D-GB-I-E-P



Our information is based on thorough research and may be considered reliable, although not legally binding.

PI 20/11/13/2023

Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de